

IDEALFIX ACRILICO

WATER-BASED WALL FIXATIVE

code A658100

DESCRIPTION

IDEALFIX ACRILICO is an acrylic wall fixative for outdoor and indoor use. It consolidates the surface and evens out the absorption. It is recommended for all paint cycles indoor, it can be used outdoor when the support is in good condition and slightly chalking.

INSTRUCTIONS FOR USE

May be applied on new and old surfaces as plaster, concrete, lime plaster, gypsum and gypsumboard.

TECHNICAL SPECIFICATIONS

- Type of binder: styrene-acrylic copolymer
- Solvent: water
- Specific gravity UNI EN ISO 2811-1: 1,00 ± 0,05 kg/l.
- Drying time (at 25 °C and 65% R.H.): to touch in 30-40 mins.; to recoat after 4 hours.

PREPARING THE SURFACE

Check the state of repair. The surface must be consistent. If this is not the case, take measures to reconstruct and strengthen the surface using specific products.

Where the surface is affected by mould, treat the surfaces with detergent and restorer anti-mould before starting.

Remove any efflorescence by buffing or washing.

Where the surface features traces of old lime-based paint or distemper, remove any parts which are flaking or which are not perfectly adherent.

Cracks must be adequately widened and filled with stucco or similar products. Use RASINT on interior.

Level any unevenness on the surface.

Remove any dust, smog or other deposits by brushing.

On dried surface apply IDEALFIX ACRILICO.

After at least 4 hours, proceed with the application of the finishing product.

APPLICATION INSTRUCTIONS

- Tools: brush, roller or spraying.
- The product is thinned at a different ratio according to the level of absorption of the surface, and in no case at less than 6 parts of water per one of fixative. The correct quantity can be estimated by observing the formation of a cloudy patina on the surface treated. Excessive quantities may form a compact layer which impairs the adhesion of subsequent coats of paint. Vice versa, too little fixative makes application difficult, with subsequently greater consumption of the product, decreased adhesion power of the finish and possible unevenness of absorption.
- Tools must be washed immediately after use with water.
- Indicative spreading rate: apply 1 litre of fixative for approx. 50-60 m2 of surface featuring average absorption. It is advisable to determine the actual consumption by performing a preliminary test on the specific surface.
- Air and support surface conditions:
Air temperature: Min. +8 °C / Max. +35 °C
Relative environmental humidity: <80%
Support surface temperature: Min. +5 °C / Max. +35 °C

Moisture level of the support surface: <10%

- Avoid applying when surface condensation is present, or in direct sunlight.

TINTING

The product cannot be tinted.

STORAGE

Maximum temperature for storage stability: +30 °C

Minimum temperature for storage stability: +5 °C

The product should be preferably used within 2 years from date of manufacture when stored in original unopened containers and in appropriate temperature conditions.

SAFETY RULES

EU limit value (Dir. 2004/42/EC)

Cat. A/g: primers (water base): 30 g/l (2010)

IDEALFIX ACRILICO Contains max: 30 g/l VOC

Use the product according to current standards of hygiene and safety; after use do not litter containers, allow the residue to dry and treat them as special waste.

For more information see the safety data sheet.

SPECIFICATION ITEM

Applications, on previously prepared surfaces, of IDEALFIX ACRILICO water-borne acrylic masonry fixative based on styrene-acrylic resin, suitable for impregnating walls of a quantity determined by the absorption of the surface.

Supply and application of the material €..... per m2.

COLORIFICIO SAN MARCO guarantees that the information herein is provided to the best of its technical and scientific knowledge and based on its experience; nonetheless, the company may not be held liable for the results obtained using these products, as application conditions are beyond its control. It is recommended to always make sure that the product is suited to each specific instance. The present sheet voids and replaces any previously existing sheets. For further technical information call the technical service +39 041 4569322.