

SUPERLIQUIGUM PEDONABILE

WATERPROOFING MEMBRANE WITHSTANDING FOOT TRAFFIC

code A718000

DESCRIPTION

SUPERLIQUIGUM PEDONABILE is a waterproofing membrane withstanding foot traffic suitable for outdoor use. Based on styrene-acrylic resins, it creates a film with high elasticity, anti-slip and sound absorbing thanks to special rubber microgranules. Suitable for the protection of cement roofing outstanding foot traffic, fibrate concrete and bituminous membranes.

INSTRUCTIONS FOR USE

It can be applied outdoor on concrete walkable substrates.

TECHNICAL SPECIFICATIONS

Type of binder: styrene-acrylic copolymers in aqueous solution

It contains rubber granules (25% on a dry basis)

Specific gravity per UNI EN ISO 2811-1: 1.00 ±0.05 kg/l.

Drying time (at 25 °C and 65% R.H.): superficial after 24 hours, in depth according to the thickness applied; to recoat after at least 24 hours.

PREPARING THE SURFACE

The hardness of cement or fibre-reinforced cement based substrates must be carefully assessed.

If the surface is slightly brittle, one should: for interior, reinforce the substrate by applying IDEALFIX water based primer. for exterior, intervene by applying ISOLPLAST R210 solvent-based primer. (Dilutions of the insulator and the amount to apply are based on the absorption of the substrate and are determined by means of preliminary tests on the specific substrate).

If mold is present, treat the surface with a suitable detergent, such as COMBAT 333 (San Marco product).

Then apply SUPERLIQUIGUM PEDONABILE to the dry and dust-free surfaces following the instructions given on the technical data sheet.

APPLICATION INSTRUCTIONS

The product must be applied by brush, by roller, by spray gun or airless.

Do not dilute when applying by brush or roller. Dilute 15% with water for spray applications.

For airless applications, the dilution varies with the type of nozzle and operating pressure.

The product is applied in at least 2-3 coats; wait approximately 24 hours between coats.

Do not apply the product when the relative humidity of the environment is >80% and the moisture of the substrate >10%, and when the temperature of the environment and/or substrate is below +5°C or above +35°C.

Avoid applying the product when exposed to direct sunlight.

After application, exterior surfaces must be protected from rain and moisture until the product has dried (normally about 48 hours at 20°C).

Clean the equipment immediately after use with water.

The spreading rate varies with the type of substrate, which on average is 0.8 - 1 m²/litre at work completed. This

coverage rate refers to smooth substrates with medium absorption; the actual coverage rate should therefore be determined by performing a preliminary test on the specific substrate.

TINTING

The product is available in the following colours: grey and red oxide.

STORAGE

Maximum temperature for storage stability: +30 °C

Minimum temperature for storage stability: +5 °C

The product should be preferably used within 2 years from date of manufacture when stored in original unopened containers and in appropriate temperature conditions.

SAFETY RULES

Limit value EU (Dir. 2004/42/EC)

Cat. A/i: One-pack performance coating (water-base): 140 g/l (2007) / 140 g/l (2010)

The product contains max: 100 g/l VOC

Use the product according to current standards of hygiene and safety; after use do not litter containers, allow the residue to dry and treat them as special waste.

For more information see the safety data sheet.

SPECIFICATION ITEM

Waterproof membrane

Applications, on concrete surfaces or reinforced one already prepared, of walkable waterproof membrane SUPERLIQUIGUM PEDONABILE, based on acrylic resins with high elasticity, in the quantities required.

Supply and application of the material €..... per sqm.

COLORIFICIO SAN MARCO guarantees that the information herein is provided to the best of its technical and scientific knowledge and based on its experience; nonetheless, the company may not be held liable for the results obtained using these products, as application conditions are beyond its control. It is recommended to always make sure that the product is suited to each specific instance. The present sheet voids and replaces any previously existing sheets. For further technical information call the technical service +39 041 4569322.

ABC è un marchio del Colorificio San Marco Spa - Via Alta 10 - 30020 Marcon (VE) - Tel 041.4569322

