

ABC STUK

POWDER PUTTY

code A008900

DESCRIPTION

ABC STUK is a powder putty to be used indoors for leveling the imperfections located on wall and wood. Suitable for filling cracks and gaps and to level the surface. Easy to sand, it provides a good anchor base for finishing paints.

INSTRUCTIONS FOR USE

May be applied on new and old plasters, concrete, gypsum. May be applied on woodwork, before a covering painting system is employed.

TECHNICAL SPECIFICATIONS

-Type of Binder: fast-drying gypsum, retarders and setting regulators

-Appearance: white powder

-Drying time (at 25 C and 65% R.H.): to sand after 3-4 hours; to recoat after 6 hours.

COATABILITY: with all emulsion paints after fixative.

PREPARING THE SURFACE

- Make sure that the surface has a maturing time of at least 28 days.

- Check the state of repair. The surface must be consistent. If this is not the case, take measures to reconstruct and strengthen the surface using specific products.

- Remove any efflorescence by buffing or washing.

- Where the surface features traces of old paint, remove any parts which are flaking and which are not perfectly adherent, whilst thick coats of lime-based paint or distemper must be removed completely by wetting the surface thoroughly and scraping, or using a water cleaning machine.

- Apply ABC STUK by means of successive passes with a plastering trowel to level and fill in order to achieve surface smoothing, or using a putty knife in order to fill the cracks and depressions.

- Proceed with the application of the fixative, chosen on the basis of the type of paint used for the finishing system.

APPLICATION INSTRUCTIONS

Air and surface conditions:

Air temperature: Min. +5 C / Max.+35 C.

Relative humidity of the air: <80%.

Temperature of the surface: Min. +5 C / Max. +35 C.

- The product can be applied using a putty knife or plastering trowel.

- Thinning: mix 100 parts of the product with 50-55 parts of water.

- Pot life of the mixture: 1 and a half hours

- Tools should be cleaned immediately after use using water.

- Indicative spreading rate: highly variable depending on the type of surface. It is advisable to perform a preliminary test on the specific surface in order to determine the actual consumption.

TINTING

The product cannot be tinted.

STORAGE

Maximum temperature for storage stability: +30 °C

Minimum temperature for storage stability: +5 °C

Stability in the original closed containers stored at suitable temperatures: 1 year.

SAFETY RULES

Does not fall under EU directive 2004/42 (legislative decree 161/2006).

Use the product according to current standards of hygiene and safety; after use do not litter containers, allow the residue to dry and treat them as special waste.

For more information see the safety data sheet.

SPECIFICATION ITEM

Applications, on preprepared interior surfaces, of ABC STUK powder wall filler based on fast-drying gypsum, retarders and setting regulators, for levelling imperfections on walls.

COLORIFICIO SAN MARCO guarantees that the information herein is provided to the best of its technical and scientific knowledge and based on its experience; nonetheless, the company may not be held liable for the results obtained using these products, as application conditions are beyond its control. It is recommended to always make sure that the product is suited to each specific instance. The present sheet voids and replaces any previously existing sheets. For further technical information call the technical service +39 041 4569322.

ABC è un marchio del Colorificio San Marco Spa - Via Alta 10 - 30020 Marcon (VE) - Tel 041.4569322

