# A7180 - SUPERLIQUIGUM PEDONABILE - LINEA ABC

Revision nr.5 Dated 18/5/2015 Printed on 18/5/2015 Page n. 1 / 7

# Safety data sheet

# SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **A7180** 

Product name SUPERLIQUIGUM PEDONABILE - LINEA ABC

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use WALL PAINT

1.3. Details of the supplier of the safety data sheet

Name COLORIFICIO SAN MARCO S.P.A.

Full address Via Alta 10

District and Country 30020 MARCON (VE)

ITALY

Tel. +39 041 4569322 Fax +39 041 5950153

e-mail address of the competent person

responsible for the Safety Data Sheet

sicurezza.prodotti@sanmarcogroup.it

1.4. Emergency telephone number

For urgent inquiries refer to Technical information: COLORIFICIO SAN MARCO SPA +39 041 4569322

(Monday - Friday 9.00-12.30; 13.30-17.00)

# **SECTION 2. Hazards identification.**

### 2.1. Classification of the substance or mixture.

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to EC Regulation 1907/2006 and subsequent amendments.

2.1.1. Regulation 1272/2008 (CLP) and following amendments and adjustments.

Hazard classification and indication: --

2.1.2. 67/548/EEC and 1999/45/EC Directives and following amendments and adjustments.

2.2. Label elements.

Hazard pictograms: -

Signal words: --

Hazard statements:

**EUH210** Safety data sheet available on request.

EUH208 Contains: reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and

2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

1,2-benzisothiazol-3(2H)-one

May cause allergic reactions.

Precautionary statements: -

2.3. Other hazards.

Information not available.

# A7180 - SUPERLIQUIGUM PEDONABILE - LINEA ABC

Revision nr.5 Dated 18/5/2015 Printed on 18/5/2015 Page n. 2 / 7

# **SECTION 3. Composition/information on ingredients.**

#### 3.1. Substances.

Information not relevant.

#### 3.2. Mixtures.

Contains:

Identification. Conc. %. Classification 67/548/EEC. Classification 1272/2008 (CLP).

2-BUTOXYETHANOL

CAS. 111-76-2 3 - 3.5 Xn R20/21/22, Xi R36/38

Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332,

Eye Irrit. 2 H319, Skin Irrit. 2 H315

Flam. Liq. 3 H226

EC. 203-905-0 INDEX. 603-014-00-0 Reg. no. 01-2119475108-36

1-METHOXY-2-PROPANOL ACETATE

CAS. 108-65-6 0,05 - 0,1 R10

EC. 203-603-9 INDEX. 607-195-00-7 Reg. no. 01-2119475791-29

Note: Upper limit is not included into the range.

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

 $T+= Very\ Toxic(T+),\ T=Toxic(T),\ Xn=Harmful(Xn),\ C=Corrosive(C),\ Xi=Irritant(Xi),\ O=Oxidizing(O),\ E=Explosive(E),\ F+=Extremely\ Flammable(F+),\ F=Highly\ Flammable(F),\ N=Dangerous\ for\ the\ Environment(N)$ 

# **SECTION 4. First aid measures.**

#### 4.1. Description of first aid measures.

EYES: Remove contact lenses, if present Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

# 4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

# 4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

# **SECTION 5. Firefighting measures.**

#### 5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide and chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use water.

### 5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If large quantities of the product are involved in a fire, they can make it considerably worse. Do not breathe combustion products.

### 5.3. Advice for firefighters.

**GENERAL INFORMATION** 

In the case of fire, use jets of water to cool the containers to prevent the risk of explosions (product decomposition and excess pressure) and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Remove all containers containing the product from the fire, if it is safe to do so.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

# A7180 - SUPERLIQUIGUM PEDONABILE - LINEA ABC

Revision nr 5 Dated 18/5/2015 Printed on 18/5/2015 Page n. 3/7

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

# SECTION 6. Accidental release measures.

### 6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

### 6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

# **SECTION 7. Handling and storage.**

### 7.1. Precautions for safe handling.

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment

### 7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s).

Information not available.

# SECTION 8. Exposure controls/personal protection.

# 8.1. Control parameters.

Regulatory References:

United Kingdom EH40/2005 Workplace exposure limits. Containing the list of workplace exposure limits

for use with the Control of Substances Hazardous to Health Regulations (as amended).

Éire Code of Practice Chemical Agent Regulations 2011. OEL EU

Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive

2000/39/EC.

**TLV-ACGIH ACGIH 2012** 

1-METHOXY-2-PROPANOL ACETATE											
Threshold Limit Value.											
Туре	Country	TWA/8h		STEL/15min							
		mg/m3	ppm	mg/m3	ppm						
WEL	UK	274	50	548	100						
OEL	IRL	275	50	550	100	SKIN					
OEL	EU	275	50	550	100	SKIN					

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

### 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protection equipment, make sure that the workplace is well aired through effective local aspiration.

# A7180 - SUPERLIQUIGUM PEDONABILE - LINEA ABC

Revision nr.5 Dated 18/5/2015 Printed on 18/5/2015 Page n. 4 / 7

#### HAND PROTECTION

Protect hands with category I (ref. Directive 89/686/EEC and standard EN 374) work gloves, such as those in latex, PVC or equivalent. The following should be considered when choosing work glove material: degradation, breakage times and permeation. Work glove resistance to preparations should be checked before use, as it can be unpredictable. Gloves' limit depends on the duration of exposure.

#### SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (ref. Directive 89/686/CEE and standard EN 344). Wash body with soap and water after removing overalls.

### RESPIRATORY PROTECTION

If the threshold value (if available) for one or more of the substances present in the preparation for daily exposure in the workplace or to a fraction established by the company's prevention and protection service is exceeded, wear a mask with an A or universal filter, the class (1, 2 or 3) of which must be chosen according to the limit concentration of use (ref. standard EN 141).

The use of respiratory tract protection equipment, such as masks like that indicated above, is necessary to reduce worker exposure in the absence of technical measures. The protection provided by masks is in any case limited.

If the substance in question is odourless or its olfactory threshold is higher than the relative exposure limit and in the event of an emergency, or when exposure levels are unknown or the concentration of oxygen in the workplace is less than 17% volume, wear self-contained, open-circuit compressed air breathing apparatus (ref. standard EN 137) or fresh air hose breathing apparatus for use with full face mask, half mask or mouthpiece (ref. standard EN 138).

### **EYE PROTECTION**

Use of protective airtight goggles (ref. standard EN 166) recommended.

# **SECTION 9. Physical and chemical properties.**

### 9.1. Information on basic physical and chemical properties.

Appearance liquid Colour color palette characteristic Odour Odour threshold. Not available. Not available. pH. Melting point / freezing point. Not available. Initial boiling point. Not available. Not available. Boiling range. Flash point. 60 °C. Not available. **Evaporation Rate** Flammability of solids and gases Not available. Not available. Lower inflammability limit. Upper inflammability limit. Not available. Lower explosive limit. Not available. Not available Upper explosive limit. Vapour pressure. Not available. Vapour density Not available. Relative density. 1.000 Ka/l Solubility Not available. Partition coefficient: n-octanol/water Not available. Auto-ignition temperature. Not available. Decomposition temperature. Not available Viscosity Not available. Explosive properties Not available. Oxidising properties Not available.

# 9.2. Other information.

Information not available

# SECTION 10. Stability and reactivity.

#### 10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

1-METHOXY-2-PROPANOL ACETATE: stable but with the air it may slowly develop peroxides that explode with an increase in temperature.

2-BUTOXYETHANOL: decomposes in the presence of heat.

# 10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

# 10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

#### EN

# COLORIFICIO SAN MARCO S.P.A.

# A7180 - SUPERLIQUIGUM PEDONABILE - LINEA ABC

Revision nr.5 Dated 18/5/2015 Printed on 18/5/2015 Page n. 5 / 7

# SECTION 10. Stability and reactivity. .../>>

1-METHOXY-2-PROPANOL ACETATE: may react violently with oxidising agents and strong acids and alkaline metals. 2-BUTOXYETHANOL: can react dangerously with: aluminium, oxidising agents. Forms peroxide with air.

#### 10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

1-METHOXY-2-PROPANOL ACETATE: store in an inert atmosphere, sheletered from moisture because it hydrolises easily. 2-BUTOXYETHANOL: avoid exposure to sources of heat and naked flames.

#### 10.5. Incompatible materials.

1-METHOXY-2-PROPANOL ACETATE: oxidising agents, strong acids and alkaline metals.

### 10.6. Hazardous decomposition products.

2-BUTOXYETHANOL: hydrogen.

# **SECTION 11. Toxicological information.**

# 11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

1-METHOXY-2-PROPANOL ACETATE: the main way of entry is the skin, whereas the respiratory way is less important owing to the low vapour tension of the product. Concentrations above 100 ppm cause eye irritation, nose and oropharynx. At 1000 ppm disturbance in the equilibrium and severe eye irritation is observed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and ocular irritation on direct contact. No chronic effects have been reported in man.

1-METHOXY-2-PROPANOL ACETATE

LD50 (Oral). 8530 mg/kg Rat LD50 (Dermal). > 5000 mg/kg Rat

2-BUTOXYETHANOL

 LD50 (Oral).
 615 mg/kg Rat

 LD50 (Dermal).
 405 mg/kg Rabbit

 LC50 (Inhalation).
 2,2 mg/l/4h Rat

# **SECTION 12. Ecological information.**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation.

### 12.1. Toxicity.

Information not available.

### 12.2. Persistence and degradability.

Information not available.

# 12.3. Bioaccumulative potential.

Information not available.

# 12.4. Mobility in soil.

Information not available.

### 12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

#### 12.6. Other adverse effects.

Information not available.

# A7180 - SUPERLIQUIGUM PEDONABILE - LINEA ABC

Revision nr.5 Dated 18/5/2015 Printed on 18/5/2015 Page n. 6 / 7

# **SECTION 13. Disposal considerations.**

### 13.1. Waste treatment methods.

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Avoid littering. Do not contaminate soil, sewers and waterways.

**CONTAMINATED PACKAGING** 

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

# **SECTION 14. Transport information.**

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

# **SECTION 15. Regulatory information.**

15	1 Safoty	hoalth	and anvir	onmontal i	rogulations	/logiclation	enocific fo	r the substance	or mivturo
10.	i. Saieiv	. nealth	and envir	onmeniai i	eaulalions	/ieuisiaiion	Specific to	r ine substance	a or mixiure.

Seveso category. None.

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

None.

Substances in Candidate List (Art. 59 REACH).

None.

Substances subject to authorisarion (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 689/2008:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None

Healthcare controls.

Information not available.

# 15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

# **SECTION 16. Other information.**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3 Flammable liquid, category 3 Acute Tox. 4 Acute toxicity, category 4 Eye Irrit. 2 Eye irritation, category 2 Skin Irrit. 2 Skin irritation, category 2 H226 Flammable liquid and vapour. H302 Harmful if swallowed. H312 Harmful in contact with skin. H332 Harmful if inhaled H319 Causes serious eye irritation. H315 Causes skin irritation.

**EUH210** Safety data sheet available on request.

Text of risk (R) phrases mentioned in section 2-3 of the sheet:

R10 FLAMMABLE.

# A7180 - SUPERLIQUIGUM PEDONABILE - LINEA ABC

Revision nr.5 Dated 18/5/2015 Printed on 18/5/2015 Page n. 7 / 7

### SECTION 16. Other information. .../>>

R20/21/22 R36/38 HARMFUL BY INHALATION, IN CONTACT WITH SKIN AND IF SWALLOWED.

IRRITATING TO EYES AND SKIN.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation.

# **GENERAL BIBLIOGRAPHY**

- 1. Directive 1999/45/EC and following amendments
- 2. Directive 67/548/EEC and following amendments and adjustments
- 3. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 4. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 5. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 6. Regulation (EC) 453/2010 of the European Parliament
- 7. Regulation (EC) 286/2011 (II Atp. CLP) of the European Parliament
- 8. The Merck Index. 10th Edition
- 9. Handling Chemical Safety
- 10. Niosh Registry of Toxic Effects of Chemical Substances
- 11. INRS Fiche Toxicologique (toxicological sheet)
- 12. Patty Industrial Hygiene and Toxicology
- 13. N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- 14. ECHA website

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

# Changes to previous review:

The following sections were modified:

01/02/03/04/05/06/07/08/09/10/11/12/15/16.