

# WOODWORK CERATO

SATIN FINISH FOR WOOD FOR INDOOR AND OUTDOOR USE

code A588300

## DESCRIPTION

Protective for wood based on alkyd resins suitable for the protection of all types of wood. Easy and quick to apply, it creates a superficial protective film and is waterproofing without flaking over time.

## INSTRUCTIONS FOR USE

Applicable on new or previously painted wood, both indoor and outdoor, such as beading, attics, windows, balconies, fences, shutters, etc...

ATTENTION to treatments on woods rich in tannin (i.e. chestnut) that may show dark spots.

## TECHNICAL SPECIFICATIONS

- Type of Binder: alkyd resin in mixture of aliphatic hydrocarbons.
- Specific gravity per UNI EN ISO 2811-1: 0.92±0.02 kg/l
- Gloss per UNI EN ISO 2811-1: 30±10 at 60°
- Drying time (at 25 C and 65% R.H.): dust free in 2 hours; to touch in 8 hours; to recoat after 24 hours.

## PREPARING THE SURFACE

Lightly sand the surface to remove the coarser fibers of the wood.

- Remove any wood resin using a suitable thinner.
- Remove any coats of old flaking paint and rough up all painted surfaces.
- Fill the imperfections with synthetic putty. Sand putty and remove dust.
- In the case of highly absorbent wood or irregular absorption it is advisable to apply a base coat of WOODWORK IMPREGNANTE.
- Proceed with the application of WOODWORK CERATO sanding between one coat and another to remove the raised fibers.

## APPLICATION INSTRUCTIONS

- Do not apply at relative humidity >80% and surface humidity >10%, and environment temperatures and/or substrate below +5°C or above +35°C.
- Avoid applying in the presence of condensation on the surface or in direct sunlight.
- Mix the product thoroughly before application.
- Tools: brush, roller
- Dilution: ready to use
- Number of coats: 2: in particularly severe atmospheric conditions, or with very absorbent surfaces, it is advisable to apply 3 coats.
- Tools should be cleaned with white spirit immediately after use.
- Indicative spreading rate: 8-10 sqm/l per coat (It is advisable to perform a preliminary test on the specific surface to determine the consumptions).

## TINTING

The product is available uncolored.

## STORAGE

Maximum temperature for storage stability: +30 °C  
Minimum temperature for storage stability: +5 °C  
The product should be preferably used within 3 years from date of manufacture when stored in original unopened containers and in appropriate temperature conditions.

## SAFETY RULES

Limit value EU (Dir. 2004/42/EC)  
Cat. A/e: interior/exterior trim varnishes and woodstains (sb): 400 g/l (2010)  
WOODWORK CERATO contains max: 400 g/l VOC

Flammable liquid and vapour. / May cause drowsiness or dizziness. / Harmful to aquatic life with long lasting effects. / Repeated exposure may cause skin dryness or cracking.  
The product must be transported, used and stored in accordance with the standards in force regarding hygiene and safety. Consult the safety sheet for additional information.

## SPECIFICATION ITEM

Applications, on already prepared wood surfaces, of waterproof finish for wood for indoor and outdoor use WOODWORK CERATO, based on modified alkyd resins, at least into 2 coats in quantities according to the absorption of wood.  
Supply and application of the material €..... per sqm.

*COLORIFICIO SAN MARCO guarantees that the information herein is provided to the best of its technical and scientific knowledge and based on its experience; nonetheless, the company may not be held liable for the results obtained using these products, as application conditions are beyond its control. It is recommended to always make sure that the product is suited to each specific instance. The present sheet voids and replaces any previously existing sheets. For further technical information call the technical service +39 041 4569322.*

ABC è un marchio del Colorificio San Marco Spa - Via Alta 10 - 30020 Marcon (VE) - Tel 041.4569322

